



ANTI-MOSQUITO COATING

Insecticide free – Safe & Eco-Friendly



VECTORCIDE SHIELD

Product description

Vectorcide SHIELD Coating is a unique, safe and highly effective treatment for indoor application. Once applied it will protect you from mosquitoes for over 12 months, keeping you, your family and friends safe from vector-borne diseases, such as malaria and dengue.

Technology

The coating seals the capsules within the surface as it dries. (Typically, over 20 billion capsules per square metre) When the mosquito clings on the VC RP2 Coating treated surface [trampling], the 'pin-like' legs of the insect puncture the capsules.

Using our unique release mechanism, the whole insect is covered in a number of technically advanced ingredients, including the repellent.

Once affected, it will not continue to bite its prey and will fly away to die.

Vectorcide International have developed RP2 after a number of years of development to counteract the increasing incidence of resistance within mosquito populations.

Packaging

Retail pack sizes available in ;

- 1 litre bottle
- 5 litres drums

For B2B customers;

- 25 litres
- 50 litres
- 200 litres HDPE carbuoys

Application

Vectorcide SHIELD can be applied by roller or brush onto clean hard surfaces such as walls, ceilings and any area where mosquitoes may rest. Do not dilute.

This material gives 100% repellency on painted surfaces for 6 – 12 months after application (as per modified WHO chamber method/OOPTS hand in cage methods) and progressively the effect reduces with age.

The treated surfaces can be wiped to remove dirt. If more aggressive cleaning is taken, it should be repainted with Vectorcide SHIELD, to restore the efficiency. We recommend repainting the interior surfaces every 12 months for maximum efficacy.

We guarantee this format free from all synthetic insecticides like Permethrin, DEET etc. and is recommended for premium interior paint application as a topcoat.

Special Precautions

Vectorcide SHIELD is a ready to use clear, coating for interior painting on walls and ceilings.

This coating contains fixated Herbal Mosquito Repellent in such quantities that it can repel mosquitoes from landing on the painted surface for up to 1 year after application and drying.

If a mosquito should land on the surface it will break some of the capsules and release further repellent.

The mosquito repellent active is of herbal origin containing the essential oils and herbs, eucalyptus oil, citronella oil, and their cyllised distilled fractions.

Content of actives in the "as is" supplied formulation is roughly 36%. The remainder of the ingredients are inert substances including water.



ADVANCED ANTI-MOSQUITO PAINT

Insecticide free – Safe & Eco-Friendly

VECTORCIDE SHIELD



Ingredients

The mosquito repellent active is of herbal origin containing essential oils and herbs like eucalyptus oil, citronella oil, and their cyclised distilled fractions.

There are NO insecticides or pesticides used in this product.

Storage

Vectorcide SHIELD is stable for 24 months when properly stored in closed containers at 25°C.

There may be slight stratification which disappears instantly on slight shaking. This is normal and is dependent upon the density of the encapsulated active.

Properties

Ionic nature:	Anionic to slightly Anionic.
Physical Appearance:	White to off-white flowable liquid. Colour is characteristic of the encapsulated active.
pH (as is):	6.5 to 8.0
Solubility in water at 25°C:	Readily dispersible.
Storage stability:	Vectorcide SHIELD is stable for 18 months when properly stored in closed containers at 25°C. There may be slight stratification which disappears instantly on slight shaking. This is normal and is dependent upon the density of the encapsulated active.
Particle Size:	PSD of Capsule-Msules = 5-15 micron D50
Capsule Content:	5% typical. Non-volatile Solids of 3-5% typical.
Ecology/ Toxicology:	No evidence of skin sensitization in sponsored study. Classified as Low relative acute toxicity (EC50 > 100 mg/L). Biodegradable in activated sludge.
Handling:	The usual hygiene and safety rules for handling chemicals should be observed in handling, storage and use of the product. The product must not be swallowed. Materials are available generally as liquid products with up to 60% water (for flowability and ease of use reasons). The usual restrictions and handling procedures in air cargo applicable to liquids.